

 <b>TRADEBE</b>	<b>Technical Data Sheet and Specification</b>	<b>iso-Butanol</b>
		<b>80001507</b>

<b>Technical Data</b>  	Formula	C <sub>4</sub> H <sub>10</sub> O
	Molecular Weight (g/mol)	74.122
	Boiling Point (Range)	108°C
	Flashpoint (closed cup)	28°C
	Auto Ignition Temperature	427°C
	Explosive Limits	1.7-10.9%
	Solubility in Water	Partial
	Water solubility in solvent	0.87%
	Refractive Index	1.3959

Product Specification	Limits	Test Method
SG @20°C	0.801-0.803	P72, P78
Water Content % w/w	0.2% maximum	P86
GC Assay % w/w	99.0% minimum iso-Butanol	P36
Appearance	10 HU maximum	P19
Solids % w/w	0.005%	P69

<b>Hazard Data</b>		<b>GHS</b>
<b>CAS no:</b>	78-83-1	<b>Danger</b> H226, H315, H318, H335, H336 P210, P370+378, P403+235, P501, P240, P241, P242, P243, P280, P302+352, P362, P305+351+338, P310, P261, P271, P403+233, P405, P233, P303+361+353, P264, P332+313, P304+340
<b>EU Index:</b>	603-108-00-1	
<b>EC no:</b>	201-148-0	
<b>MSDS no:</b>	464	
		

UN No:	UN Class:	PG	EAC Code:	HIN No:	UK Tunnel code:	Packaging Supplied in
1212	3	III	3Y	30	(D/E)	Bulk, Isotank, PG III Drum

Note: Shelf life 12 months

Customer Sign..... TSR Sign.....  
 Date..... Date.....

This information is accurate to the best knowledge of the Company. Tradebe Solvent Recycling (TSR) Limited accepts no liability whatsoever arising out of the use of the information or any use, application, adaptation or processing of the product described herein	First issued:	08/12/2009
	Rev. no:	5
	Rev. issue Date:	15/03/2016